

Index

Symbols

- `*`, in server reply 31
- `*`, wildcard for LIST 300
- `..`, as mailbox separator (Cyrus) 205, 235, 238
- `/`, as mailbox separator (Cyrus) 205, 235, 238
- `%` (wildcard), for LIST 300
- 8-bit characters *see* eight-bit characters

A

- `a` (permission) 37
- access permissions *see* ACLs
- access time, of a file *see* `atime`
- account options *see* user options (Courier)
- ACLs 34, 36, 37, 154
 - Cyrus 231, 232
 - group-based (Courier) 144
 - identifier 154
 - IMAP extension 34, 316
 - activating (Courier) 102
 - listing (Cyrus) 272
 - manipulating (Courier) *see* `maildiracl` (tool)
 - negative permissions 155
 - removing (Cyrus) 272
 - saving in Courier *see* `courierimapacl` (file)
 - setting (Cyrus) 272
 - switching off at filesystem level 58
 - for virtual domains (Cyrus) 236, 237
- active directory with user data 81
- `ADDRESS` (Courier parameter) 98
- `address` (Sieve command) 246
- administration directory (Cyrus) 203
- administrator, creating (Cyrus) 194
- `admins` (Cyrus option) 203, 287, 288
- aggregator 51, 281–290
 - backend server 282, 286–287
 - frontend server 282–285
- `allowanonymouslogin` (Cyrus option) 203
- `allowsubscribes` (Cyrus option) 287
- `allowusermoves` (Cyrus option) 287
- `altnamespace` (Cyrus option) 277
- annotation database (Cyrus) 259
- `annotation_db` (Cyrus parameter) 259
- `annotations.db` (file) 267, 278
- `\Answered` (flag) 35
 - in the filename (`maildir`) 113
 - searching for 305
- APOP 27, 28, 148
 - POP3 command 317, 319
- AppArmor 193
- `APPEND` (IMAP command) 302
- Apple Mail 279
- `aquota.user` (file) 168
- arbitron 263
- `arbitronsort.pl` (tool) 190, 269
- `atime`, switching off 57–58, 64
- attachments, retrieving individually (IMAP) 310
- AUTH (IMAP extension) 315
- AUTH (POP3 command) 317, 319
- AUTH=PLAIN (capability) 296
- `authcram` (Courier) 120, 129, 144, 148
- `authcustom` (Courier) 121, 130
- `authdaemon` (Courier)
 - activating 99
 - configuration file *see* `authdaemonrc`
 - starting 88
 - daemon 20, 121–123
 - configuration file *see* `authdaemonrc`
 - custom authentication modules *see* `authcustom`
 - `authcustom`
 - using with Cyrus SASL 189, 213

- authdaemonrc (Courier configuration file) 95, 123, 134, 145
 - AUTHENTICATE (IMAP command) 218, 297
 - Authenticated (IMAP status) 32
 - available commands 298–303
 - switching to 303
 - Authenticated Post Office Protocol *see* APOP
 - authentication *see* logging in
 - by fingerprint 213
 - by hash values instead of passwords 213
 - by iris scan 213
 - Cyrus 207–224
 - via Kerberos 212, 214, 223–224
 - via LDAP 212–214, 220–223
 - via MySQL 213, 216–220
 - via PAM 219–220
 - via SQL database 213
 - daemon (Courier) *see* authdaemond
 - choosing method (POP3) 319
 - choosing method (Courier) 99, 122
 - IMAP commands 297
 - library (Courier) *see* Courier Authlib
 - password in cleartext 210
 - POP3 commands 317
 - programs, custom (Courier) 121
 - proxy (Courier) *see* authdaemond
 - authennumerate 160
 - tool 138, 145
 - authldap (authentication module for Courier) 121, 140–146
 - caching requests 122
 - authldaprc (file) 95, 140
 - authlib 120–144
 - AUTHMODULES (Courier parameter) 99, 122, 123
 - authmysql (authentication module for Courier) 120, 133–139, 144, 147
 - caching requests 122
 - authmysqlrc (file) 134–139
 - authorization state (POP3) 317
 - authpam (Courier) 120, 123–124
 - authpgsql
 - authentication module for Courier 120, 139, 140, 144, 147
 - caching requests 122
 - file 139
 - authpipe (Courier) 121, 131–133
 - authProg (authentication tool) 131
 - authpwd (authentication module for Courier) 120, 143
 - authshadow (authentication module for Courier) 120, 143
 - authstest (tool) 121–122
 - authuserdb (authentication module for Courier) 120, 124–129, 144
 - authvchkpw (authentication module for Courier) 120
 - autocreate_sieve_script (Cyrus option) 251
 - autocreatequota (Cyrus option) 203, 226, 251
 - autologout timer, resetting 296
 - auxprop (Cyrus SASL module) 189, 194, 213
 - LDAP connection via 220, 221
 - MySQL connection via 216
 - availability 19, 43–51
 - avelsieve (Squirrelmail plugin) 244
- ## B
- backup (IMAP folders) 29
 - backup (main Cyrus database) 278
 - backup/ (directory) 278
 - BALANCE (iptables) 47
 - Bcc header, searching in 305
 - benchmark tools 55
 - berkeley (Cyrus database format) 259
 - berkeley-nosync (Cyrus database format) 259
 - berkeley_cachesize (Cyrus parameter) 258
 - berkeley_txns_max (Cyrus parameter) 258
 - block size, for NFS 64
 - body
 - retrieving (IMAP) 310
 - retrieving partially (IMAP) 311
 - retrieving partially (POP3) *see* TOP (POP3 command)
 - searching in 305
 - bonnie 55
 - byte-octet conversion 296
- ## C
- c (permission) 37
 - CA *see* certificate authority (CA)
 - cache proxy 51, 73–74
 - cached IMAP *see* offline IMAP
 - CAPA (POP3 command) 319
 - capabilities 33

- for encrypted communication (IMAP) 297
 - polling (IMAP) 296
 - polling (POP3) 319
 - specifying for Courier 100
- CAPABILITY (IMAP command) 175, 295, 296, 314
 - for encrypted communication 297
- case sensitive
 - folder names 301
 - search 40
- Cc header, searching in 306
- cell phone (and IMAP) 176, 273
- certificate authority (CA) 208
 - list in email clients 208
 - trustworthy 208
- certificates *see* SSL certificates
- challenge-response procedure 129, 148, 242, 297
- change time, of a file *see* ctime
- character encoding, considering during a search 305
- character set, considering during a search 305
- CHECK (IMAP command) 303
- CHILDREN (IMAP extension) 34, 315
- chk_cyrus 264
- chmod, influence on c and mtime 57
- cleartext
 - login *see* LOGIN (IMAP command)
 - passwords 81
- client, workaround for faulty 101
- CLOSE (IMAP command) 32, 303
- cluster 20
 - Cyrus 281, 291
- Cluster filesystem, as email repository 45
- CLUSTERIP (iptables) 47
- cm *see* createmailbox
- com_err.h (Common Error library) 329
- compile_sieve (tool) 268
- compiling
 - Courier 321, 324
 - Cyrus 325, 330
- CONCAT (SQL command) 137
- conditional query (Sieve) *see* if (Sieve)
- Cone 85
- config2header (tool) 269
- config2man (tool) 269
- configdirectory
 - Cyrus option 203
 - Cyrus parameter 270
- configuration parameters
 - Courier 96–105
 - reading out (Courier) 100
- connection
 - information, caching (SSL) 260
 - keeping open *see* NOOP
 - terminating
 - automatically for POP3 (Cyrus) 259
 - with IMAP *see* LOGOUT (IMAP command)
 - with POP3 *see* QUIT (POP3 command) 318
 - unintended (IMAP) 32
 - testing *see* NOOP
- contents, of an email *see* body
- convert-sieve.pl (tool) 190, 269
- COPY (IMAP command) 313
 - using the Unique ID 313
- Courier 18, 85–179
 - configuration 95–105
 - configuring SSL encryption 102–105
 - crashing 93
 - vs. Cyrus 20–21
 - downloading 322
 - IMAP proxy 50, 145
 - installation 86–87
 - installing from the source code 321, 324
 - migration problems 110
 - misleading reply to LIST (POP3) 25
 - MTA 85
 - paths 87
 - project 85
- Courier Authlib 85
- Courier team
 - reaction to bug reports 93
 - reaction to change requests 110
- courierimapacl (file) 109, 154–155
- courierimapkeywords (directory) 116
- courierimapsubscribed (file) 109
- courierlogger (tool) 98, 103
- couriertcpd 88
 - specifying command-line parameters 98
- COURIERTLS (Courier parameter) 104
- couriertls (tool) 87, 104
- CPU *see* processor
- CRAM 129
- CRAM-MD5 100, 119, 148, 214

- using with Cyrus 213
- when testing the login with `imtest` 218
- CRAM-SHA1 100, 119, 148
- CRAM-SHA256 148
- crash, Courier 93
- CREATE (IMAP command) 300
- createmailbox
 - `cyradm` command 239
 - `cyradmin` command 272
- creating users
 - Cyrus 194
 - with `saslpasswd2` 194
- Crispin, Mark 33
- crypt
 - hash, instead of cleartext password 119
 - as password hash algorithm 147
- ctime 57
- `ctl_cyrusdb` (tool) 266
- `ctl_deliver` 266
- `ctl_mboxlist` 266
- cur
 - for creating directories 88
 - for listing contents of a directory 108, 112
 - for listing purpose of a directory 108
- `cvt_cyrusdb` 267
- `cyr_expire` (tool) 202, 268
- `cyradm` (tool) 21, 194, 271–274, 277
 - setting quotas 228
 - setting up shared folders 230
- `cyrdump` (tool) 267
- Cyrus 18, 183–291
 - activating SSL support 210
 - administration information 277–280
 - as administration tool *see* `cyradm`, (tool)
 - allowing anonymous users 203
 - connecting to MySQL 213, 216–220
 - connecting to PostgreSQL 213
 - vs. Courier 20–21
 - creating an administrator 194
 - creating users 194
 - with `saslpasswd2` 194
 - directory hierarchy 187
 - downloading 325
 - encrypting access data 189
 - and firewalls 191, 220
 - function test 195–197
 - IMAP proxy 51
 - installation 184–187
 - under Debian 186
 - under Red Hat 186
 - from source code 325, 330
 - under SuSE 185
 - LMTP *see* LMTP
 - location in the filesystem 204
 - lowercase addresses 204
 - maximum email size 204
 - Murder cluster 51, 281–290
 - ports 191
 - and Postfix 191–197
 - project origins 183
 - Red Hat source RPM for 186
 - refusing to accept email (quota) 204
 - SASL authentication methods 205
 - Sieve directory 205
 - SSL certificates 205
 - user vs. Unix system account 215
 - working directory 188
- Cyrus (IMAP server)
 - data security 255, 257
 - domain administrators 237
 - notify daemon 252
 - operating with other MTAs 254, 255
 - sorting email 237
 - specifying a timeout 205
 - virtual domains 232
- Cyrus Aggregator *see* aggregator
- Cyrus SASL *see* `libsasl`
 - library 190
- `cyrus-admin-2.2` (Debian package) 186
- `cyrus-clients-2.2` (Debian package) 186
- `cyrus-common-2.2` (Debian package) 186
- `cyrus-imap-utils` (Red Hat package) 186
- `cyrus-impd`
 - Red Hat package 186
 - SuSE package 185
- `cyrus-impd-2.2` (Debian package) 187
- `cyrus-murder-2.2` (Debian package) 187
- `cyrus-nntpd-2.2` (Debian package) 187
- `cyrus-pop3d-2.2` (Debian package) 187
- `cyrus-sasl`
 - package 189
 - Red Hat package 186
- `cyrus-sasl-crammd5` (SuSE package) 185
- `cyrus-sasl-digestmd5` (SuSE package) 185

- cyrus-sasl-otp (SuSE package) 185
 - cyrus-sasl-plain
 - Red Hat package 186
 - SuSE package 185
 - cyrus-sasl-saslauthd (SuSE package) 185
 - cyrus-sasl-sqlauthprop (SuSE package) 185
 - cyrus.cache (file) 276
 - cyrus.conf 188, 199–202, 266
 - checkpoint 202
 - cleanup 202
 - configuring
 - the mupdate server 288
 - the murder backend 287
 - the murder frontend 285
 - defining the LMTP socket 191
 - delprune 202
 - EVENTS{} section 201–202, 260, 268
 - idled 200
 - imap 201
 - listen 200, 201
 - lmtprun 201, 254
 - lmtprun 254
 - notify 201, 253
 - pop3d 201
 - recovering 200
 - SERVICES{} section 200–201, 210, 241, 254, 285, 288
 - sieve 201, 241
 - specifying nice values for events 268
 - START{} section 200
 - structure 199
 - tlsprun 202
 - cyrus.header (file) 256, 276
 - cyrus.index (file) 276
- D**
- d (permission) 37
 - dam *see* deleteaclmailbox
 - data (Squirrelmail directory) 70
 - data loss, through ReiserFS 54
 - data protection 159
 - data segment, limiting size of (Courier) 102
 - database format
 - annotation database (Cyrus) 259
 - berkeley-nosync (Cyrus) 260
 - converting (Cyrus) 267
 - duplicate database (Cyrus) 260
 - possible (Cyrus) 259
 - quota database (Cyrus) 260
 - quotalegacy (Cyrus) 260
 - subscription database (Cyrus) 260
 - date
 - as search criterion 305, 307
 - determining the internal (IMAP) 311
 - format in IMAP commands 305
 - db.backup1/ (directory) 278
 - db/ (directory) 278
 - DEBUG_LOGIN (Courier parameters) 81, 99, 122
 - debugging, an IMAP implementation 303
 - default domain (Cyrus) 234
 - DEFAULT_DOMAIN (Courier parameter) 138, 139
 - defaultdelivery (QMail configuration file) 94
 - defaultdomain (Cyrus option) 203, 234
 - DEFAULTOPTIONS (Courier parameter) 145
 - defaultpartition (Cyrus option) 239
 - DEFDOMAIN (Courier parameter) 98
 - DELE (POP3 command) 26, 318
 - DELETE (IMAP command) 301
 - delete permission *see* ACLs
 - deleteaclmailbox (cyradmin command) 272
 - \Deleted (flag) 31, 32, 35, 303, 304
 - searching for email with 40, 306
 - number of 31
 - deletemailbox (cyradmin command) 272
 - deleting
 - email (IMAP) 39, 298, 303, 304
 - email (POP3) 26, 318
 - folders (IMAP) *see* DELETE (IMAP command)
 - undoing the deletion of email (POP3) 26, 318
 - deliver
 - Cyrus service 255
 - tool 268
 - deliver databases (Cyrus) 266
 - deliver.db (file) 266, 278
 - deliverquota
 - MDA 173
 - tool 87
 - denial-of-service attack 166
 - preventing (Courier) 97, 102
 - dialup, and IMAP 29
 - DIGEST-MD5 (password-transfer method) 214
 - using with Cyrus 213, 242
 - when using an LDAP server 221
 - dir_index (mount option) 58–60

